

Fax 312-938-0118

PRELIMINARY ASSESSMENT/ VISUAL SITE INSPECTION

CBI RESEARCH CORPORATION PLAINFIELD, ILLINOIS ILD 082 939 588

FINAL REPORT

Prepared for

U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Waste Programs Enforcement Washington, DC 20460

Work Assignment No. : R05032

EPA Region : 5

 Site No.
 :
 ILD 082 939 588

 Date Prepared
 :
 December 8, 1992

Contract No. : 68-W9-0006 PRC No. : 309-R05032-IL39

Prepared by : Resource Applications, Inc.

(Peter McLaughlin)

Contractor Project Manager : Shin Ahn

Telephone No. : (312) 856-8700 EPA Work Assignment Manager : Kevin Pierard

Telephone No. : (312) 886-4448

TABLE OF CONTENTS

Section	<u>, </u>	Page
EXEC	CUTIVE SUMMARY	ES-1
1.0	INTRODUCTION	. 1
2.0	FACILITY DESCRIPTION	. 4.
	2.1 FACILITY LOCATION 2.2 FACILITY OPERATIONS 2.3 WASTE GENERATING PROCESSES 2.4 HISTORY OF DOCUMENTED RELEASES 2.5 REGULATORY HISTORY 2.6 ENVIRONMENTAL SETTING	. 4 . 7 . 13
	2.6.1 Climate 2.6.2 Flood Plain and Surface Water 2.6.3 Geology and Soils 2.6.4 Ground Water	. 16 . 16
à.	2.7 RECEPTORS	18
3.0	SOLID WASTE MANAGEMENT UNITS	. 20
4.0	AREAS OF CONCERN	25
5.0	CONCLUSIONS AND RECOMMENDATIONS	26
REFE	RENCES	30
Attach	<u>iment</u>	
A	VISUAL SITE INSPECTION SUMMARY AND PHOTOGRAPHS	٠
В	VISUAL SITE INSPECTION FIELD NOTES	
C	FACILITY'S RCRA PART A PERMIT APPLICATION	

LIST OF TABLES

<u>Table</u>	1	Page
1	SOLID WASTE MANAGEMENT UNITS (SWMU)	. 8
2 .	SOLID WASTES	11
3	SWMU SUMMARY	27
	LIST OF FIGURES	
Figure	<u>I</u>	Page
1	FACILITY LOCATION	5
2	FACILITY LAYOUT/SWMU LOCATIONS	. 9

ENFORCEMENT CONFIDENTIAL

EXECUTIVE SUMMARY

Resource Applications, Inc. (RAI) performed a preliminary assessment and visual site inspection (PA/VSI) to identify and assess the existence and likelihood of releases from solid waste management units (SWMU) and other areas of concern (AOC) at the CBI Research Corporation (CBI Research) facility in Plainfield, Illinois. This summary highlights the results of the PA/VSI and the potential for releases of hazardous wastes or hazardous constituents from SWMUs identified.

The CBI Research facility performs research and development (R & D) projects for the parent company, Chicago Bridge & Iron Company (Chicago Bridge & Iron). No manufacturing processes are conducted at the facility. Numerous RCRA-listed wastes were, are, and may be generated during R & D activities. Hazardous wastes, such as waste degreasers (F002), waste paint (F003, F005), waste paint-related materials (F003, F005), and spent solvent (F003); and nonhazardous waste oils and spent coolants are generated in small quantities during R & D activities. These wastes are accumulated in the Hazardous Waste Accumulation Area (SWMU 1) located in the basement near the machining area. Once full, the unit is taken to the Hazardous Waste Storage Pad (SWMU 2) for less than 90-day storage; however, according to the facility representative this unit has not been filled since it began operation in 1986. In the past, hazardous wastes generated during R & D activities were placed in the Hazardous Waste Storage Tank (SWMU 3). When the tank was full, the hazardous waste was pumped into 55-gallon steel drums which were then stored at SWMU 2 in preparation for off-site disposal. The facility also generated a number of characteristic "D" wastes, "P" wastes, and "U" wastes during inventory cleanouts. These wastes are lab-packed and stored at SWMU 2 prior to off-site disposal. In addition to the hazardous wastes, the facility has generated asbestos waste during an inspection of the cooling tower. An asbestos sludge was placed in a 70gallon steel salvage drum and placed on a wooden pallet in the materials yard. This Asbestos Waste Storage Area (SWMU 4) will be emptied of all asbestos waste upon completion of an asbestos abatement project scheduled to begin in March 1992. This asbestos abatement project and the removal of all asbestos waste will be conducted by Universal Asbestos Removal (UAR) of Bridgeview, Illinois. UAR will dispose of the asbestos waste at ARF Landfill in Grayslake, Illinois.

The facility has operated at its current location since 1967. The facility occupies 130 acres in an industrial and agricultural area and employs about 80 people. The facility's regulatory status is

that of a small-quantity generator. The facility underwent a name change in 1985 from Chicago Bridge & Iron Company to CBI Research Corporation. The name change did not affect ownership or operations. Prior to the current owners, the facility was operated by Continental Can Company, Inc. (CCC). CCC constructed the current laboratory building in 1959 and operated the facility until 1963. The facility was dormant from 1963 to 1967 when Chicago Bridge & Iron Company began operations. Prior to 1959 the site was agricultural land.

The facility is planning to undergo RCRA closure for its Hazardous Waste Storage Pad (SWMU 2) and its Hazardous Waste Storage Tank (SWMU 3), which rests on SWMU 2. According to the facility representative, it is Chicago Bridge & Iron corporate policy to seek formal RCRA closure for all regulated waste management units no longer in use. Closure is being conducted since SWMU 3 has not been utilized since 1986. SWMU 2 is being closed because it contains SWMU 3. Soil sampling will be performed around the perimeter of SWMU 2. If contamination is detected above IEPA cleanup objectives and it becomes necessary to remove SWMU 2, a temporary hazardous waste storage area will be designated in an inactive paint spray booth in the basement of the laboratory building. SWMU 3 will be removed during closure.

The PA/VSI identified the following 4 SWMUs and one AOC at the facility:

Solid Waste Management Units

- 1. Hazardous Waste Satellite Accumulation Area
- 2. Hazardous Waste Storage Pad
- 3. Hazardous Waste Storage Tank
- 4. Asbestos Waste Storage Area

Area of Concern

Tank Farm

CBI Research is bordered on the north by agricultural land, on the west by Kerr Glass Company, on the south by agricultural land, and on the east by the DuPage River. Private residences are located on the east side of the DuPage River. Access to the facility is controlled by an 8-foothigh chain-link fence surrounding the facility.

RELEAS DATE RIN # NITIALS

ES-2

ENFORCEMENT CONFIDENTIAL

The closest surface water body is the DuPage River, which is the eastern border of the facility. The DuPage River is used for recreational and commercial purposes. The closest wetlands area is approximately 0.5 mile east of the facility, at an abandoned strip mine area.

There is a low potential for release to ground water, surface water, and on-site soils from all SWMUs. There is a moderate potential for release to air from the Asbestos Waste Storage Area (SWMU 4). This is due to the fact that the drum containing the asbestos waste is stored uncovered, outdoors; therefore the asbestos waste may become airborne. All other SWMUs have a low potential for release to air.

There is a low potential for release to ground water, surface water, and air from the Tank Farm (AOC 1). AOC 1 has a moderate potential for release to on-site soils due to the age of the tanks and since the integrity of the tanks has not been evaluated.

RAI recommends that the facility manage its asbestos waste stored at SWMU 4, so as to minimize the potential for release to environmental media. RAI also recommends integrity testing of the Tank Farm (AOC 1) tanks and/or soil sampling of AOC 1 for evidence of release. RAI recommends no further action for all other SWMUs.

RELEASED W

1.0 INTRODUCTION

PRC Environmental Management, Inc. (PRC) received Work Assignment No. R05032 from the U.S. Environmental Protection Agency (EPA) under Contract No. 68-W9-0006 (TES 9) to conduct preliminary assessments (PA) and visual site inspections (VSI) of hazardous waste treatment and storage facilities in Region 5. Resource Applications, Inc. (RAI), TES 9 team member, provided the necessary assistance to complete the PA/VSI activities for the CBI Research Corporation (CBI Research) facility.

As part of the EPA Region 5 Environmental Priorities Initiative, the RCRA and CERCLA programs are working together to identify and address RCRA facilities that have a high priority for corrective action using applicable RCRA and CERCLA authorities. The PA/VSI is the first step in the process of prioritizing facilities for corrective action. Through the PA/VSI process, enough information is obtained to characterize a facility's actual or potential releases to the environment from solid waste management units (SWMU) and areas of concern (AOC).

A SWMU is defined as any discernible unit at a RCRA facility in which solid wastes have been placed and from which hazardous constituents might migrate, regardless of whether the unit was intended to manage solid or hazardous waste.

The SWMU definition includes the following:

- RCRA-regulated units, such as container storage areas, tanks, surface impoundments, waste piles, land treatment units, landfills, incinerators, and underground injection wells
- Closed and abandoned units
- Recycling units, wastewater treatment units, and other units that EPA has generally exempted from standards applicable to hazardous waste management units
- Areas contaminated by routine and systematic releases of wastes or hazardous constituents. Such areas might include a wood preservative drippage area, a loading-unloading area, or an area where solvent used to wash large parts has continually dripped onto soils.

An AOC is defined as any area where a release to the environment of hazardous waste or constituents has occurred or is suspected to have occurred on a nonroutine and nonsystematic basis. This includes any area where such a release in the future is judged to be a strong possibility.

The purpose of the PA is as follows:

- Identify SWMUs and AOCs at the facility.
- Obtain information on the operational history of the facility.
- Obtain information on releases from any units at the facility.
- Identify data gaps and other informational needs to be filled during the VSI.

The PA generally includes review of all relevant documents and files located at state offices and at the EPA Region 5 office in Chicago.

The purpose of the VSI is as follows:

- Identify SWMUs and AOCs not discovered during the PA.
- Identify releases not discovered during the PA.
- Provide a specific description of the environmental setting.
- Provide information on release pathways and the potential for releases to each medium.
- Confirm information obtained during the PA regarding operations, SWMUs, AOCs, and releases.

The VSI includes interviewing appropriate facility staff, inspecting the entire facility to identify all SWMUs and AOCs, photographing all visible SWMUs, identifying evidence of releases, initially identifying potential sampling parameters and locations, if needed, and obtaining all information necessary to complete the PA/VSI report.

This report documents the results of a PA/VSI of the CBI Research facility in Plainfield, Illinois. The PA was completed on March 2, 1992. RAI gathered and reviewed information from the Illinois Environmental Protection Agency (IEPA) and from EPA Region 5 RCRA files. RAI also reviewed documents from the U.S. Department of Agriculture (USDA), U.S. Geological Survey (USGS), and the Federal Emergency Management Agency (FEMA). The VSI was conducted on March 3, 1992. It included interviews with a facility representative and a walk-through inspection of the facility. Four SWMUs and one AOC were identified at the facility.

The VSI is summarized and six inspection photographs are included in Attachment A. Field notes from the VSI are included in Attachment B.

2.0 FACILITY DESCRIPTION

This section describes the facility's location, past and present operations (including waste management practices), waste generating processes, history of documented releases, regulatory history, environmental setting, and receptors.

2.1 FACILITY LOCATION


The CBI Research facility is located at 1501 N. Division Street in Plainfield, Will County, Illinois (latitude 41°37'25" N and longitude 88°12'07" W), as shown in Figure 1. The facility occupies 130 acres with the plant grounds occupying 10 acres. The facility is located in an agricultural and industrial area.

The CBI Research facility is bordered on the north by agricultural land, on the west by Kerr Glass Company, on the south by agricultural land, and on the east by the DuPage River. There are private residences on the east side of the DuPage River.

2.2 FACILITY OPERATIONS

The CBI Research facility performs research and development (R & D) projects for their parent company, Chicago Bridge & Iron Company (Chicago Bridge & Iron), which is a subsidiary of CBI Industries, Inc. The projects being conducted at the facility include: marine research, utilizing a large wave tank for testing scaled, off-shore structures; integrity tests on structural steel tanks and vessels; and systems testing. CBI Research also performs feasibility tests on independent projects. There is no manufacturing or production occurring at the facility.

Most chemical raw materials are stored in the inactive wet laboratory. These are in small amounts and stored in glass jugs and jars, and metal containers. Raw material solvents, oils, and coolants are stored in the basement machine shop and the maintenance department. Oils and coolants are stored in 55-gallon steel drums. Solvents, stored in 16-ounce spray cans, are used for cleaning tools and other equipment associated with the construction of test models. Large metal structures,



such as tanks and vessels, are stored outdoor in the materials yard. The facility also stores old raw materials in three staging areas.

The first staging area is the inactive spray paint booth (not in use since approximately 1981) located in the plant basement (see Photograph No. 1). Old raw material is kept in this area until it can be properly identified and its usefulness determined. If the material is found to be unusable it is managed as waste. This staging area is storing an assortment of materials including glues, paints, petroleum products, and cement mix.

The second staging area is located outdoors in the materials yard. This area has 14 55-gallon steel drums (some in over-packs), two 35-gallon steel drums, and four 70-gallon steel drums (see Photograph No. 2). All the drums are on wooden pallets above gravel covering. The material in this staging area was to be used for a discontinued research project for developing an orange juice concentrate system. According to the facility representative, this material may be ethylene glycol, liquid smoke, and/or orange juice. This material will be identified, and if found to be unusable, will be managed as waste.

The third staging area is a 20-foot long metal transport container located north of the second staging area (see Photograph No. 3). This staging area contains materials used in the construction of a structure erected by Chicago Bridge & Iron in the Persian Gulf during the early 1980s. According to the facility representative, the material is currently considered raw material and will be subject to the same usefulness determination as the materials in the other two staging areas. If found to be unusable, the materials will be managed as waste.

The facility has an aboveground Tank Farm (AOC 1) consisting of three tanks: one 18,500-gallon steel floating-roof tank, which stored petroleum products; one 11,500-gallon steel tank which stored ethylene glycol; and one 11,000-gallon concrete tank, which stored liquified natural gas (LNG). The petroleum product and LNG tanks have not been used since 1981. The ethylene glycol tank was emptied in 1990 and is no longer in use. The tank farm was used to perform emissions testing on floating-roof tanks. No releases from these tanks have been documented; however, neither integrity tests nor soil sampling have been performed for these tanks.

The facility has operated at its current location since 1967 and employs about 80 people. The facility underwent a name change in 1988 from Chicago Bridge & Iron to CBI Research Corporation (CBI Research, 1985). Facility activities were not affected. The facility consists of the 78,000-square-foot (sq.-ft.) laboratory building, the 1.25-million-gallon wave tank, the 37,000-sq.-ft. insulation research building, and the 2-acre materials storage yard. Currently the facility is constructing a new 75,000-sq.-ft. engineering building adjacent to the north side of the laboratory building. The facility has also constructed a retention pond west of the new engineering building to collect storm water runoff.

The facility building was constructed by Continental Can Company, Inc. (CCC) in 1959. CCC operated the facility as a glass research center from 1959 to 1963. The facility was dormant from 1963 to 1967 when Chicago Bridge & Iron began operations. Prior to 1959 the area was used as agricultural land.

Hazardous wastes, and nonhazardous waste oils and spent coolants generated during R & D activities are accumulated in a 55-gallon steel drum Hazardous Waste Satellite Accumulation Area (SWMU 1) in the basement near the machining area. When the drum is full, it is taken outdoors to the Hazardous Waste Storage Pad (SWMU 2). Formerly, the facility would store hazardous wastes in the Hazardous Waste Storage Tank (SWMU 3); however this tank has not been used since 1986. The facility also generates hazardous waste during inventory cleanouts. These wastes are lab-packed and stored at SWMU 2 prior to off-site disposal. Facility SWMUs are identified in Table 1. The facility layout, including SWMUs and AOC, is shown in Figure 2.

2.3 WASTE GENERATING PROCESSES


Hazardous wastes are generated at the CBI Research facility during R & D activities, and inventory cleanouts. However, types of hazardous wastes generated and rates of generation are not typical. In general terms, the primary waste streams generated at the facility in recent years are waste degreasers (F002), waste paint (F003, F005), waste paint-related material (F003, F005), spent solvent (F003), waste corrosives (D002, D003, D005), waste oxidizers (D001, D003, D007, D009), waste flammable liquids (D001, F003), waste poisons (D003, D005, D006, D009), and waste compressed gas (D001), as well as characteristic "P" wastes, and characteristic "U" wastes. The

TABLE 1
SOLID WASTE MANAGEMENT UNITS (SWMU)

SWMU Number	SWMU Name	RCRA Hazardous Waste Management Unit*	Status
1	Hazardous Waste Accumulation Area	No	Active; accumulating hazardous wastes.
2	Hazardous Waste Storage Pad	Yes	Active; storing hazardous wastes for less than 90 days; will undergo RCRA closure.
3	Hazardous Waste Storage Tank	Yes	Inactive; will undergo RCRA closure.
4	Asbestos Waste Storage Area	No	Active; storing asbestos waste.
	•		

Note:

^{*} A RCRA hazardous waste management unit is one that currently requires or formerly required submittal of a RCRA Part A or Part B permit application.



facility also generates nonhazardous waste oils and spent coolants. Wastes generated at the facility, as well as the waste source and primary management unit are listed in Table 2.

During R & D activities various wastes are generated. Machine and tool cleaning generates waste degreasers (F002). Painting models and other equipment generate waste paints (F003, F005) and waste paint-related material (F003, F005), as well as spent solvent (F003). Nonhazardous waste oils and spent coolants from the machining area are also generated. As these wastes are generated, they are placed in a 55-gallon steel drum at the Hazardous Waste Satellite Accumulation Area (SWMU 1) located in the basement near the machining area. Most of the recent R & D work performed at CBI Research has not required much waste generation activity. SWMU 1 was installed in 1986 and has never been filled. Once full, this unit will be moved to the Hazardous Waste Storage Area (SWMU 2). Prior to the installation of SWMU 1, these R & D generated wastes were taken to the Hazardous Waste Storage Tank (SWMU 3). When necessary, the waste was pumped from SWMU 3 into 55-gallon steel drums and stored in SWMU 2. The waste was removed for incineration by SCA Chemical Services of Chicago, Illinois. The last time SWMU 3 was emptied was 1986, when seven 55-gallon steel drums were removed from the facility.

In recent years, most of the facility's waste generation has been from inventory cleanouts. Out-dated, off-specification, or obsolete material is identified and lab-packed for removal. In 1991, Safety-Kleen Corporation (Safety-Kleen) of Dolton, Illinois removed 275 gallons of waste paint-related material (F003, F005) from the facility. Safety-Kleen incinerated this waste. Also in 1991, the following wastes were lab-packed and removed by FIW, Inc. (FIW) of Pecatonica, Illinois: 190 gallons of waste corrosives (D002, D003, D005), 45 gallons of waste oxidizers (D001, D003, D007, D009), 390 gallons of waste flammable liquids (D001, F003), 25 gallons of waste poisons (D003, D005, D006, D009), and 5 gallons of waste compressed gas (D001). All of these hazardous wastes were incinerated at FIW.

The facility may also generate a number of characteristic "P" waste, and characteristic "U" wastes during inventory cleanouts or R & D activities. Typically, these waste are lab-packed or placed in 55-gallon steel drums and stored at SWMU 2 prior to off-site disposal. Hazardous wastes possibly generated at the facility are listed on the facility's revised RCRA Part A permit application which is included as Attachment C. In 1990, the facility emptied the ethylene glycol

TABLE 2 SOLID WASTES

Waste/EPA Waste Code	Source	Primary Management Unit*
Waste Degreasers/F002	Research and Development	1, 2, and 3
Waste Paints/F003, F005	Research and Development	1, 2, and 3
Waste Paint-Related Material/ F003, F005	Research and Development, and Inventory Cleanouts	1, 2, and 3
Spent Solvent/F003	Research and Development	1, 2, and 3
Waste Corrosives/D002, D003, D005	Inventory Cleanouts	2
Waste Oxidizers/D001, D003, D007, D009	Inventory Cleanouts	2
Waste Flammable Liquids/D001, F003	Inventory Cleanouts	2
Waste Poisons/D003, D005, D006, D009	Inventory Cleanouts	2
Waste Compressed Gas/D001	Inventory Cleanouts	2
Characteristic "P" Wastes	Research and Development, and/or Inventory Cleanouts	2
Characteristic "U" Wastes	Research and Development, and/or Inventory Cleanouts	2
Waste Oil/NA**	Research and Development, and/or Inventory Cleanouts	1, 2, and 3

TABLE 2 (continued)

SOLID WASTES

Waste/EPA Waste Code	Source	Primary Management Unit*
	•	
Spent Coolant/NA**	Research and Development, and/or Inventory Cleanouts	1, 2, and 3
Asbestos/NA**	Cooling Tower Inspection	4
Ethylene Glycol/NA**	Research and Development, and Inventory Cleanouts	2
		*

Notes:

^{*} Primary management unit refers to a SWMU that currently manages or formerly managed the waste.

^{**} Nonapplicable (NA) designates nonhazardous waste.

product tank located in the Tank Farm (AOC 1). Ethylene glycol had been used for emissions testing of floating-roof tanks. The ethylene glycol was deemed unusable and 385 gallons were removed by and taken to Effluent Technology, Inc. of McCook, Illinois. Effluent Technology, Inc. recycled the ethylene glycol.

Prior to 1990, while inspecting the cooling tower located on the roof of the laboratory building, facility maintenance personnel shovelled out a sludge-like substance suspected to contain asbestos and placed it in a 70-gallon steel salvage drum. This substance was analyzed by Universal Asbestos Removal (UAR) of Bridgeview, Illinois in 1992, and found to contain asbestos (CBI Research, 1992). This drum was placed on a wooden pallet at the Asbestos Waste Storage Area (SWMU 4) in the materials yard. According to the facility representative, UAR is to begin an asbestos abatement program in March 1992. UAR will remove asbestos from the laboratory building which will undergo remodelling. UAR will also remove any remaining asbestos from the cooling tower. When UAR removes all the asbestos waste from the facility, it will also remove the asbestos waste located at SWMU 4. All asbestos waste is scheduled to go to ARF Landfill in Grayslake, Illinois.

2.4 HISTORY OF DOCUMENTED RELEASES

No releases of hazardous wastes or hazardous constituents to ground water, surface water, air, or on-site soil have been documented at the facility.

2.5 REGULATORY HISTORY

Chicago Bridge & Iron submitted a notification of hazardous waste activity to EPA on August 11, 1980 (Chicago Bridge & Iron, 1980a). The facility submitted a RCRA Part A permit application on November 12, 1980 (Chicago Bridge & Iron, 1980b). This application listed the following process codes and capacities: S01 (drum storage) at 1,100 gallons, and S02 (tank storage) at 1,000 gallons. Due to the nature of the facility's activities, Chicago Bridge & Iron listed on the application all wastes that it did or may generate, as follows:

F001	U044	U165
F.005	U112	U169
P018	U123	U188
P105	U134	U190
P106	U135	U196
U001	U140	U213
U002	U147	U219
U013	U151	U220
U019	U154	U223
U021	U159	U226
U029	U161	U239

CBI Research submitted a revised RCRA Part A permit application to EPA or February 17, 1988 (CBI Research, 1988). The revised Part A reflected the following changes:

- Facility name change from Chicago Bridge & Iron to CBI Research
- Facility address change from Route 59 to 1501 N. Division St. (physical location did not change)
- Description of activities to reflect name change
- EPA hazardous waste codes F002 and D001 were added
- Process code S02 was changed to S01.

The facility is currently preparing a closure plan for its Hazardous Waste Storage Pad (SWMU 2) and Hazardous Waste Storage Tank (SWMU 3). AWARE Environmental of Charlotte, North Carolina is assisting CBI Research in the closure activities. Closure is being conducted due to the reduced hazardous waste generating activities and the subsequent lack of need for SWMU 3. The closure plan will address the removal of SWMU 3, and if warranted, the removal of SWMU 2. Although neither unit stored hazardous wastes for greater than 90 days, a Chicago Bridge & Iron corporate policy requires formal RCRA closure of any waste management unit no longer in use. SWMU 2 is being closed because it contains SWMU 3. Soil sampling will be performed around the perimeter of SWMU 2. If contamination is detected above IEPA cleanup objectives, SWMU 2 will be removed. If SWMU 2 is to be removed, the facility will utilize the spray paint booth (see Photograph No. 1) as a temporary hazardous waste storage area. At the time of the VSI, no further progress had been made regarding the closure of these units. The facility currently operates as a small-quantity generator storing wastes for less than 90 days.

In the past, CBI Research has had some RCRA compliance problems. During an inspection on February 14, 1986, IEPA noted that the facility did not have records describing the type, quantity, and final disposition of the hazardous wastes generated on site (IEPA, 1986). These violations were resolved on February 19, 1986 (IEPA, 1986). During an inspection on December 8, 1987, IEPA noted numerous paperwork violations including missing or incorrect information on the facility's Part A permit application (IEPA, 1988a). The facility submitted several responses to these violations and was found to be in compliance on April 27, 1988 (IEPA, 1988b). The facility also received a notice of violation (NOV) as a result of the December 8, 1987 inspection from the EPA regarding violations of the land disposal requirements of F-solvent wastes (EPA, 1988a). The facility submitted a response to the NOV on April 6, 1988, and was subsequently found to be in compliance (EPA, 1988b). During an inspection on December 19, 1989, the facility was found to be violating the land disposal restrictions for failure to provide written notice attached to each waste manifest leaving the facility (EPA, 1990a). The facility responded to the NOV on January 31, 1990, and was subsequently found to be in compliance (EPA, 1990b).

The facility is not required to have operating air permits. The facility does not have a history of odor complaints from area residents. The facility is not required to have a National Pollutant Discharge Elimination System (NPDES) permit.

2.6 ENVIRONMENTAL SETTING

This section describes the climate, flood plain and surface water, geology and soils, and ground water in the vicinity of the CBI Research facility.

2.6.1 Climate

The site is situated in northern Will County, Illinois, about 6 miles north-northwest of Joliet. With no significant topographical barriers to airmass flow, the climate in the area is typically continental with cold winters; warm summers; and frequent short periodic fluctuations in the temperature, humidity, cloudiness and wind direction (Ruffner, 1985). The average daily temperature is 48.7°F. The lowest average daily minimum temperature of 11.3°F occurs in January. The highest average daily maximum temperature of 84.2°F occurs in July. The prevailing wind direction is west

and the average wind speed is 10.4 miles per hour. Average annual precipitation as water equivalent is 35.62 inches. Annual net precipitation is 5.6 inches (USDC, 1968). In winter about one half of the precipitation, or 10 percent of the annual total, falls as snow. During the fall, winter, and spring, the pattern of precipitation tends to be uniform over both time and distance, whereas in summer rainfall is often locally heavy and variable. The one-year, 24-hour maximum rainfall recorded in the area over the last 25 years is 10.48 inches (Ruffner and Bair, 1985).

2.6.2 Flood Plain and Surface Water

The general direction of surface water flow is to the east into the southwardly flowing DuPage River, which is the eastern border of the facility. The facility has constructed a retention pond east of the new engineering building. The retention pond gathers the surface runoff, which is then directed eastward, toward the DuPage River. The facility is on a 100-year floodplain (FEMA, 1982). The Lily Cache Creek is approximately 0.75 mile to the east. The Des Plaines River is approximately 6 miles to the east. The DuPage and Des Plaines Rivers are used for recreational and commercial purposes, as is the Chicago Sanitary and Ship Canal, which is adjacent to the Des Plaines River.

2.6.3 Geology and Soils

No site-specific information was available for the CBI Research facility, so the following discussion, based on regional geologic information, is presented. The main features of the northeastern Illinois landscape are the result of glaciation (Bergstrom, et al., 1955). Soils are formed in glacial till with a relatively high clay content (USDA, 1980). The soil structure is fairly graded and well drained to sewers and low-lying areas. The water carrying capacity and permeability of the soil are considered moderate.

The varied glacial and bedrock materials deposited are the result of streams and rivers that flowed from the glaciers. The area is on a broad, gently sloping arch of Paleozoic bedrock formation overlain by glacial deposits, called drift. These deposits mantle most of the area and consist of unconsolidated till, silt, clay, sand, gravel, and peat (Willman, 1971). The glacial deposits form an irregular surface that covers the solid layered bedrock at the site. The drift is underlain by Silurian dolomite bedrock which lies unconformable on rocks of the Maquoketa Group.

The Cambrian system rock is marine in origin. Its lower half is largely sandstone and the upper half consists of dolomites, sandy dolomites, sandstones, and siltstones. Sandstones of the Eau Claire Formation, which dominate in the vicinity of the site, are 370 to 470 feet thick (Willman, 1971). The Eau Claire Formation is composed of a variety of rock types including sandstones, siltstones, dolomite, and shale in the upper and middle part. The lower part is composed of rock similar to Mt. Simon Sandstone, which is present throughout the area (Hughes, et al., 1966). The base is the top of Precambrian crystalline rock (Hughes, et al., 1966). The depth of crystalline rock ranges from 3,750 feet to 4,250 feet around the facility.

The thickness of the unconsolidated till ranges from 50 feet to 250 feet in the area (USDA, 1980). Shallow sand deposits are mainly fine-grained and silty; for ground water supplies, drilled wells usually penetrate solid bedrock (Bergstrom, et al., 1955).

2.6.4 Ground Water

In the vicinity of the site ground water is obtained from four major aquifers: (1) sand and gravel beds in the glacial drift; (2) shallow dolomite aquifers, mainly the Silurian Dolomite; (3) the Cambrian-Ordovician aquifer, in which the Ironton-Galesville and Glenwood-St. Peter Sandstones are the most productive units; and (4) the Mt. Simon aquifer, which consists of the Mt. Simon Sandstone and the basal sandstone of the Eau Claire Formation (Willman, 1971). Ground water flows north, northwest in the area (Village of Plainfield, 1992).

In Will County, ground water supplies are obtainable from 50 feet to 150 feet deep in sand and gravel within the glacial drift. The best possibilities for high capacity wells in sand and gravel are where the drift is generally over 100 feet thick (Bergstrom, et al., 1955). Some wells penetrate through the drift and obtain water from open cracks and crevices in the dolomite.

The shallow bedrock aquifer system yields water through fractures and solution openings and is recharged from precipitation. Shallow wells have the advantage of rapid recharge but their limitations include erratic yield because of irregular permeability and susceptibility to contamination (Hughes, et al., 1966).

The deep bedrock aquifer systems include the Cambrian-Ordovician system and the Mt. Simon system. The major aquifers are the Glenwood-St. Peter, Ironton-Galesville, and Mt. Simon Sandstones. The top of the Cambrian-Ordovician aquifer system is at the top of or within the Galena-Platteville dolomites. the Cambrian-Ordovician and the Mt. Simon aquifers are separated by relatively impermeable shales and dolomites of the upper and middle part of the Eau Claire formation and are included with the Mt. Simon sandstone as the Mt. Simon aquifer system.

The wells in the deep bedrock aquifer system yield in excess of 700 gallons per minute (gpm) and are dependable for large supplies of water. The Galena-Platteville Dolomite contributes little water because of slow permeability. The Glenwood-St. Peter Sandstone, beneath the Galena-Platteville dolomite, is widely utilized where water requirements are less than 200 gpm. It has a permeability of approximately 9 to 15 gallons per day/square-foot (gpd/sq. ft.) while the underlying Ironton-Galesville Sandstone has a permeability of about 35 gpd/sq. ft. The Mt. Simon aquifer system lies at approximately 1,650 feet below the surface and about 270 feet of fresh water-bearing sandstone can be expected. The Mt. Simon system has an average permeability of approximately 16 gpd/sq. ft. Water wells rarely penetrate more than a few hundred feet into this system because the water is too highly mineralized for most uses (Hughes, et al., 1966).

2.7 RECEPTORS

The CBI Research facility occupies 130 acres in an industrial and agricultural area in Plainfield, Illinois. Plainfield has a population of about 3,500.

The CBI Research is bordered on the north by agricultural land, on the west by Kerr Glass Company, on the south by agricultural land, and on the east by the DuPage River. Private residences are on the east side of the DuPage River. The nearest school, St. Mary's School, is located about 2 miles south of the facility. Facility access is controlled by an 8-foot high chain-link fence.

The nearest surface water body, the DuPage River, is the eastern border of the facility, and is used for recreational and commercial purposes. Other water bodies in the area include the Lily Cache Creek, located about 0.75 mile east of the facility; Lake Renwick, located about 1.5 miles south of the facility; and the Des Plaines River, located about 6 miles east of the facility.

The Village of Plainfield provides drinking water and sanitary services for the facility and the surrounding area through the use of two on-line deep wells. These two wells are located 0.5 mile west and 0.75 mile south of the facility (Village of Plainfield, 1992). Kerr Glass Company, located on the west border of the facility, maintains an industrial well.

Sensitive environments are not located on site. The nearest wetland area is located about 0.5 mile east of the facility, at an abandoned strip mine area (USDI, 1983).

3.0 SOLID WASTE MANAGEMENT UNITS

This section describes the four SWMUs identified during the PA/VSI. The following information is presented for each SWMU: description of the unit, dates of operation, wastes managed, release controls, history of documented releases, and RAI observations. Figure 2 shows the SWMU locations.

SWMU 1

Hazardous Waste Satellite Accumulation Area

Unit Description:

The Hazardous Waste Satellite Accumulation Area is located indoors, in the basement of the laboratory building, near the machining area. The unit is a 55-gallon steel drum with a metal funnel at the top (see Photograph No. 4). The unit accumulates small quantities of wastes generated during R & D activities. Once full, the drum is taken to the Hazardous Waste Storage Pad (SWMU 2). The drum is on a concrete floor. There are no floor drains near this unit.

Date of Startup:

This unit began operation in 1986.

Date of Closure:

This unit is active.

Wastes Managed:

This unit is currently managing waste degreasers (F002), waste paints (F003, F005), waste paint-related materials (F003, F005), spent solvent (F003), waste oil, and spent coolant.

Release Controls:

This unit is located indoors, on a concrete floor. There are no floor drains near this unit.

History of Documented

Releases:

No releases from this unit have been documented.

Observations:

This unit has not been filled since it began operation in 1986. The concrete floor appeared sound and there were no visual signs of cracking. No evidence of release was noted.

SWMU 2

Hazardous Waste Storage Pad

Unit Description:

The Hazardous Waste Storage Pad is located outdoors, in the materials yard, about 100 feet east of the wave tank building. This unit stores hazardous wastes (and occasionally nonhazardous wastes) for less than 90 days. The unit is a concrete pad measuring 20 feet by 15 feet with a 6-inch berm around the perimeter of the pad (see Photographs No. 5 and 6). A convexed ramp provides easy loading/unloading of drums without disrupting the secondary containment. There is an 8-foot high chain-link fence with a locked gate surrounding the unit. The Hazardous Waste Storage Tank (SWMU 3) rests on the concrete pad within the fenced unit. There are no storm drains inside the unit.

Date of Startup:

The unit began operation in 1982.

Date of Closure:

The unit is currently active; however, the facility is preparing a closure plan. According to the facility representative, closure should be completed 165 days after the start of closure activities.

Wastes Managed:

The unit manages all hazardous wastes generated at the facility. Hazardous wastes are stored in 55-gallon steel drums or in lab-packs. This unit has also stored nonhazardous ethylene glycol during a one-time tank pump-out generation. For a complete list of all wastes managed at this unit, see Attachment C.

Release Controls:

This unit has a 6-inch berm around the perimeter of the pad.

History of Documented

Releases:

No releases from this unit have been documented.

Observations:

There was no waste being stored at this unit at the time of the VSI. There is a slight crack running from east to west across the center of the pad and berm. There are two 200-gallon empty fuel oil tanks that were inadvertently brought into the unit by a former employee. No evidence of release was noted at this unit.

SWMU 3

Hazardous Waste Storage Tank

Unit Description:

The Hazardous Waste Storage Tank is located inside the Hazardous Waste Storage Pad (SWMU 2). The unit was used to store hazardous waste which was allowed to blend in order to improve fuel blending potential. Once the unit was full, the hazardous waste was pumped out and placed into 55-gallon steel drums, which were stored at SWMU 2. The unit is a 1,000-gallon aboveground steel tank with metal supports which keep the tank elevated about 3 inches above the concrete pad (see Photograph No. 6).

Date of Startup:

This unit began operations in 1982.

Date of Closure:

The unit has been inactive since 1986 and will be closed along with SWMU 2. A closure plan is being prepared and will be submitted to IEPA. The facility representative estimates that closure will be completed 165 days after the start of closure activities.

Wastes Managed:

This unit managed waste degreasers (F002), waste paints (F003, F005), waste paint-related material (F003, F005), spent solvent (F003), and nonhazardous waste oils and spent coolant.

Release Controls:

This unit rests on SWMU 2 which has a 6-inch high berm around the

perimeter of the pad.

History of Documented

Releases:

No releases from this unit have been documented.

Observations:

According to the facility representative, the only waste that may still be inside the unit is sludge. The sludge will be removed and properly disposed of during closure activities. No evidence of release was noted at this unit.

SWMU 4

Asbestos Waste Storage Area

Unit Description:

The Asbestos Storage Area is located outdoors, in the materials yard, about 100 feet north of the Hazardous Waste Storage Pad (SWMU 2). The unit is located in one of the staging areas for undetermined product. The unit stores asbestos waste generated during a cooling tower inspection. The unit consists of 70-gallon steel salvage drums resting on wooden pallets above a gravel ground cover (see Photograph No. 2).

Date of Startup:

This unit began operation in approximately 1989.

Date of Closure:

This unit is active.

Wastes Managed:

This unit manages asbestos waste.

Release Controls:

The drums used in this area are normally sealed; however, during the

VSI, one drum of asbestos waste was open.

History of Documented

Releases:

No releases from this unit have been documented.

ATTACHMENT A

VISUAL SITE INSPECTION SUMMARY AND PHOTOGRAPHS

VISUAL SITE INSPECTION SUMMARY

CBI Research Corporation Plainfield, Illinois 60544 ILD 082 939 588

Date:

March 3, 1992

Facility Representatives:

Douglas Hansen, Manager of Research Services

Inspection Team:

Peter M. McLaughlin, Resource Applications (RAI)

Alan Supple, RAI

Photographer:

Alan Supple, RAI

Weather Conditions:

Calm, overcast, temperature about 40°F

Summary of Activities:

The visual site inspection (VSI) began at 9:15 a.m. with an introductory meeting. The inspection team discussed the purpose of the VSI and the agenda for the visit. The facility representative then discussed the CBI Research facility's past and current operations, solid waste generated, and history of documented releases. Most of the information was exchanged on a question-and-answer basis. The CBI Research facility representative provided the inspection team with copies of documents requested.

The VSI tour began at 11:30 a.m. The laboratory building, wave tank, materials yard, and all materials staging areas were inspected. During this time photographs were taken of the Hazardous Waste Satellite Accumulation Area (SWMU 1), Hazardous Waste Storage Pad (SWMU 2), Hazardous Waste Storage Tank (SWMU 3), and Asbestos Waste Storage Area (SWMU 4). No AOCs were identified during the VSI.

The tour concluded at 12:45 p.m., after which the inspection team held an exit meeting with the facility representative. The VSI was completed and the inspection team left the facility at 1:15 p.m.

Observations:

During the VSI, one drum of asbestos waste was being stored. The drum was not covered. No evidence of release from this unit was noted.

4.0 AREAS OF CONCERN

RAI identified one AOC during the PA/VSI. This AOC is discussed below; its location is shown in Figure 2.

AOC 1 Tank Farm

The Tank Farm (AOC 1) consisting of three aboveground tanks: one 18,500-gallon steel floating-roof tank, which stored petroleum products; one 11,500-gallon steel tank which stored ethylene glycol; and one 11,000-gallon concrete tank, which stored liquified natural gas (LNG). The petroleum product and LNG tanks have not been used since 1981. The ethylene glycol tank was emptied in 1990 and is no longer in use. The tank farm was used to perform emissions testing on floating-roof tanks. The ground area surrounding the Tank Farm is gravel cover over soil. No releases from these tanks have been documented; however, neither integrity tests nor soil sampling have been performed for these tanks. Until the soil surrounding the tanks is sampled for evidence of release, and/or the tanks are found to be tight, this area should be considered an AOC.

5.0 CONCLUSIONS AND RECOMMENDATIONS

The PA/VSI identified four SWMUs and one AOC at the CBI Research facility. Background information on the facility's location, operations, waste generating processes, history of documented releases, regulatory history, environmental setting, and receptors is presented in Section 2.0. SWMU-specific information, such as the unit's description, dates of operation, wastes managed, release controls, history of documented releases, and observed condition, is presented in Section 3.0. AOCs are discussed in Section 4.0. Following are RAI's conclusions and recommendations for each SWMU and AOC. Table 3 summarizes the SWMUs and AOC at the CBI Research facility and recommended further actions.

SWMU 1

Hazardous Waste Satellite Accumulation Area

Conclusions:

The Hazardous Waste Satellite Accumulation Area is used to accumulate small quantities of wastes generated during R & D activities. The drum currently used at this unit has not been filled since the unit began operations in 1986. The unit is located indoors, away from floor drains, and has no history of release. The unit has a low potential for release to ground water, surface water, air, and on-site soils.

Recommendations:

RAI recommends no further action for this unit.

SWMU 2

Hazardous Waste Storage Pad

Conclusions:

The Hazardous Waste Storage Pad is used to store all hazardous wastes for less than 90 days prior to off-site disposal. No wastes were being stored at the time of the VSI. The facility is preparing a closure plan to close this unit and the Hazardous Waste Storage Tank (SWMU 3). The unit has a low potential for release to ground water, surface water, air, and on-site soils.


Recommendations:

RAI recommends no further action for this unit.

RELEASED TO

TABLE 3 SWMU AND AOC SUMMARY

	<u>SWMU</u>	Dates of Operation	Evidence of Release	Recommended Further Action
1.	Hazardous Waste Satellite Accumulation Area	1986 to present	None	No further action.
2.	Hazardoùs Waste Storage Pad	1982 to present	None	No further action.
3.	Hazardous Waste Storage Tank	1982 to 1986	None	No further action.
4.	Asbestos Waste Storage Area	Approximately 1989 to present	None	Manage waste so as to minimize potential for release.
	<u>AOC</u>	Dates of Operation	Evidence of Release	Recommended Further Action
1.	Tank Farm	1976 to 1990	None	Integrity tests of tanks and/or soil sampling for evidence of release.





SWMU 3

Hazardous Waste Storage Tank

Conclusions:

The Hazardous Waste Storage Tank was used to store and blend hazardous wastes. When full, the hazardous wastes were pumped into 55-gallon steel drums and prepared for off-site disposal. This unit is to be closed and removed due to lack of use. No releases have been documented from this unit. The unit has a low potential for release to ground water, surface water, air, and on-site soils.

Recommendations:

RAI recommends no further action for this unit.

SWMU 4

Asbestos Waste Storage Area

Conclusions:

The Asbestos Waste Storage Area stores asbestos waste generated during an inspection of the facility cooling tower. Asbestos waste is stored in a 70-gallon steel salvage drum. The asbestos waste is expected to be removed from the facility upon completion of the laboratory remodelling and cooling tower upgrade. The potential for release to environmental media is detailed below.

Ground Water: Low. Due to the nature of the waste managed, this unit has a low potential for release to ground water.

Surface Water: Low. Due to the nature of the waste managed, this unit has a low potential for release to surface water.

Air: Moderate. During the VSI, one drum of asbestos waste was stored without a lid. The asbestos may become airborne during windy conditions.

On-Site Soils: Low. Due to the nature of the waste managed, this unit has a low potential for release to on-site soils.

DATE RIN # MITIALS

ENFORCEMENT CONFIDENTIAL

Recommendations:

RAI recommends that the waste be managed in such a way as to minimize

potential for release to environmental media.

AOC 1

Tank Farm

Conclusions:

The Tank Farm stored petroleum products, LNG, and ethylene glycol used during emissions testing of floating-roof tanks. The aboveground tanks are no longer used. Neither integrity tests nor soil sampling have been performed. The area surrounding the tanks consists of gravel cover over soil. The potential for release to environmental media is detailed below.

Ground Water: Low. The tanks are empty and no longer used.

Surface Water: Low. The tanks are empty and no longer used.

Air: Low. The tanks are empty and no longer used.

On-Site Soils: Moderate. The tanks are old and their integrity is undetermined. A release to on-site soil may have occurred.

Recommendations:

RAI recommends that the integrity of the tanks be evaluated and/or the soil surrounding the tanks be sampled for evidence of release.




REFERENCES

- Bergstrom, R.E., J.W. Foster, L.F. Selkreeg, W.A. Pryor, 1955. "Groundwater Possibilities in Northeastern Illinois", Illinois State Geological Survey Circular 198, Urbana, Illinois.
- CBI Research Corporation (CBI Research), 1985. Letter notifying EPA of operator name change, March 12.
- CBI Research, 1988. Revised RCRA Part A permit application, February 17.
- CBI Research, 1992. Telephone conversation between Peter McLaughlin (RAI) and Douglas Hansen (CBI Research), March 11.
- Chicago Bridge & Iron Company (Chicago Bridge & Iron), 1980a. Notification of Hazardous Waste Activity, August 11.
- Chicago Bridge & Iron, 1980b. RCRA Part A permit application, November 12.
- Environmental Protection Agency (EPA), 1988a. Notice of Violation (NOV) regarding land disposal requirements of F-solvent wastes, March 10.
- EPA, 1988b. Letter of compliance for NOV of March 10, 1988, April 22.
- EPA, 1990a. NOV regarding inadequate waste manifests, January 24.
- EPA, 1990b. Letter of compliance for NOV of January 24, 1990, February 7.
- Federal Emergency Management Agency (FEMA), 1982. National Flood Insurance Program, Village of Plainfield, Illinois, Will County Community-Panel No. 170771 0001, November 17.
- Hughes, G.M., P. Kratz, and R.A. Landon, 1966. "Bedrock Aquifers of Northeastern Illinois".

 Illinois State Geological Survey Circular 406, Urbana, Illinois.
- Illinois Environmental Protection Agency (IEPA), 1986. Compliance Inquiry Letter (CIL) listing violations noted during a February 14, 1986 inspection, and stating compliance was met on February 19, 1986, March 21.
- IEPA, 1988a. CIL listing several violations noted during a December 8, 1987 inspection, February 5.
- IEPA, 1988b. Compliance letter for all violations noted during December 8, 1987 inspection, April 27.
- Ruffner, J.A., 1985. Climates of the States. Gale Research Company, Detroit.
- Ruffner, J.A., and E. Bair, 1985. Weather of U.S. Cities. Gale Research Company, Detroit.

- U.S. Department of Agriculture (USDA), 1980. "Will County Soils, Will County, Illinois". Soil Conservation Service/Illinois Agriculture Experiment Station.
- U.S. Department of Commerce, (USDC), 1968. <u>Climate Atlas of the United States.</u> U.S. Printing Office, Washington, D.C.
- U.S. Geological Survey (USGS) 1980a. Normantown, Illinois, Topographic Quadrangle 7.5-Minute Series.
- USGS, 1980b. Plainfield, Illinois, Topographic Quadrangle 7.5-Minute Series.
- U.S. Department of Interior (USDI), 1983. National Wetlands Inventory map, Normantown, Illinois, 1983.
- Village of Plainfield, 1992. Conversation between Rob Singh (RAI) and Harry Countyman (Village of Plainfield Water Department), March 30.
- Willman, H.B., 1971. "Summary of the Geology of the Chicago Area." <u>Illinois State Geological Survey Circular 460</u>, Urbana, Illinois.



Photograph No. 1 Orientation:

Location: Near SWMU 1

Date: 3/3/92

Description:

This inactive paint spray booth serves as a staging area for material whose usefulness needs to be determined. If the material is found to be unusable it will be managed as waste. The paint spray booth will serve as a temporary hazardous waste storage area if the Hazardous Waste Storage Pad (SWMU 2) must be removed during closure.



Photograph No. 2

Southeast

Location: SWMU 4


Date: 3/3/92

Orientation: Description:

The salvage drum on the right contains asbestos waste. All other drums are staged

and awaiting usefulness determination. If found unusable, the material will be

managed as waste.




Photograph No. 3 Location: Near SWMU 4 Orientation:

Description: This 20-foot transport container is the staging area for material that was used during a

Chicago Bridge & Iron project in the Persian Gulf. If the material is found to be

unusable, it will be managed as waste.



Photograph No. 4

Description:

Location: SWMU 1

Date: 3/3/92

Date: 3/3/92

Orientation:

This unit has not been filled since it began operation in 1986. Wastes generated

during R & D activities are accumulated here.




Photograph No. 5

Orientation:

Description:

Date: 3/3/92 This unit will undergo RCRA closure. The two 200-gallon fuel oil tanks are empty.

No wastes were being stored here at the time of the VSI.



Photograph No. 6

Orientation:

Location: SWMU 2 and SWMU 3

Date: 3/3/92

Location: SWMU 2

Description: This unit rests on the Hazardous Waste Storage Pad (SWMU 2). It will undergo

RCRA closure and be removed. It has not stored hazardous waste since 1986.

ATTACHMENT B

VISUAL SITE INSPECTION FIELD NOTES

50 3 3 9 Z CB | RESOLECTA 9:15 CURRENTLY PREPARITY CLOSURE PUND PUR THOUSE WET CHEM LAB IS CURRISHIPLY MINCHIVE TANK FARM - ISMPTY - WERE USED FUR EMISSIVES TESTIME - PRIED PROPULTS - ETAYLEIN LLYCOL : LAST CONTUNS DRUP TEST CAVIT 1989 CUERBETTLY VEDER CONSTRUCTION; - ENGINGERING BLOW -3 STIRY 75 1100 PTZ - OH ULD PARKING LUT POTENTIAN BASIN FOR SPORM WATER 1991 130 ACA 63 DUPALE ZIVER : EAST BORDER SANTIARY SENGE PLANTFIELD TRUTINGS WHAS GW. WELL @ KORR GLASS BLDG BUILT BY CONT GAN 1959 DURN-PAIT 1963 - 1967 1467 - (3) PRIVA TO 1954 - ALLEND BASHINGHT - LINES SPRAY BUNTIH - OLUT VSHILL (STIPLING METL) MACINING SHUP

er o services missibilità diad de ominata la la societe e de dont establica contidada de la didaca de actes intra contentra teg

		59
BASILG PROCESSES FOOD		11
MACINIS GROVE	OR OFF-SLOPE STRUCK	W65
- PAISILD LITEST		
7 14 2100 6 1000		
STURULTURISL KOSDSELIA		
7 64624 66623 110	08 BLOG	
PRUSEUTS RESENDENCY O	ROUP	
- PAOCES RELITED	Work	
- CONLEPTUAL PLA	HS (PILUT)	
DEVISEDEN MUST GROVE		
	PEUDUCTS	
	UR EVISA ON PITTIA	444
18 MAUSING -2 405		
CLD PAINT (RODICE	5	
ETHYLKING CLYCOL UN	1-51-6111111111111111111111111111111111	
ONE-IME CONER	27) A 11/1/11/12/12/12/12/12/12/12/12/12/12/12	
LABYALL OFF- SPECY	OLD CHEMS	
Hay M. Mant 5 Plek	>	

59 SUIDSTG FLAM LIB 385 1 PODI / PUP3 WASTE CORPUSING 145 L DOUZ WASTE COMPRESSED GAS SEQ DOO TODO LOOK DOON TO SOLD DOON TO WILL LET COPY OF WASTE MAINET POR 91 I'IW, INK. PEUTONICA IL - INCINIATE OLD CHIMS SUMS SMALL & WASTE DILS & COULDING ASSESS AS SECTIFILLIASTIC TO AFR UNIDFILL GRAYSLAILE UNIVERSAL ASBESTOS REMOVEL - BRIDLEVIEW ILL EINYLONE alyCOL: BEALDON TECHINOGY me CCOIC, IL PAINT WASTE SAPETY-KLEEN DOLTON, IL 41111 FROCES WIZE PUL THEAMPL ENERGY SOULCE MORINI NURIH - CLASSIFIED CRYSTIAL LIRAWIA 3/3/02 Rose M: My of

47.4 1 1 1 m

60
FAUL 19 1 3 7 ENELDYS 2 60
111111111111111111111111111111111111111
275 TO NEW 546 BYLLO
NU BELEASES
CLUSURE OVE TU LACK OF USE
THIS ENLED WENTER CHAPOLINE NO
NXDET PROPES OU FUR 15T SUBMIT TO DUIN
LP2-1-60m 6 1486
THAK WILL BE ROWNED
SCA CHIST ICAL SEVICES CHICAGNIL
1-
1 ZEMOVE PAG
TEMO SECTA IN SECTO PRINTIBUILI
PROPOSED DETE OF COMPLETION !!
1165 DUGS PROMISTRATION
PLANTELD - 3500 GOUPLE
DOURTS STORED FUR TO 5745
WY 425 5 1044 Q 4 92.
3) 3) 92 D- M M 6 h

JULY MINISTER JULI

ter in ter eine ferte beite der beitert beite ferte ferte beite beite beite beite beite beite beite beite beite 62 STAINING HRUDS: - serpy Bruits - 30th CINTAMER W MAIL YARD - trums JAIR LINE CRACK IN PAD RETENTION WER FLOW WOUND GO TO RIVER BERM ELESS PEUPSEM LEASED TO PARMER WASTE DT NOI 1979 CHILARD BLIDLES IRON CO 1985 CBI RESKARCH CIKP DIL TILNES VS1 11:30 OILS ORGANICS 91 1157 5704065 DUMINO INTO SATOLLIKE OR LAB PALK S. OME WATER SAMPLES IN LAB OTHERS BEING STAGEP () E SCRPY BUTH LOW BAY PORSIAN GULFI DAS STALING FOR PRODUCTS TO BE OUTMIND PAINTS, PETRO PROPUCTS QUE (2) N SCRAL METAL CARBON S.S. ALUM - RULLY ROCYC. (3) N H.W. ALCUM: BESEMONT VARILETY OF WASTES GIEN. 43/92 Rock. My che 3/3/92 Part Winht

ATTACHMENT C FACILITY'S RCRA PART A PERMIT APPLICATION

SPLAINFIELD 1460544

VII. SIC COOSE integer, in order of priority of the property o		是此是这些是是是一种。 第一年,第一年,第一年,第一年,第一年,第一年,第一年,第一年,第一年,第一年,
A, FIRST		ECONO
73443 (BOILER SHOP)		CONSTRUCTION NOT
C. THIRD		SPECFIED & R &D
ii ' ' ' '(ipecify)		
	7	
VIII. OPERATOR INFORMATION		
A. NAME		B. is the name listed in
BCBI RESEARCH CORPORATI	ON	Item VIII-A size the owner? YES NO
10 10		14 46
C. STATUS OF OPERATOR (Enter the appropriate letter into the ann	ver box; if "Other", specify.)	D. PHONE (area code & no.)
F = FEDERAL M = PUBLIC (other tran jederal or suite) S = STATE O = OTHER (specify) P = PRIVATE	PRIVATE A	815 436 2912
E. STREET OR P.O. BOX		
1501 N. DIVISION STREET		
F. CITY OR TOWN	GISTATE H. ZIP CODE IX. IF	VDIAN LAND
BPLAINFIELD	IL 60544 " "	e facility located on Indian lands? YES AO
10 10	46 41 48 47 - 31	32
X EXISTING ENVIRONMENTAL PERMITS		
	us from Proposed Sources)	
9 N 9 P		
B. UIC (Underground Injection of Fluids) E. OTHI	LR (specify)	
9 0 9	(specify)	
	ER (specify)	
9 RI ILD 0 8 2 9 3 9 5 8 8 9 1 1	(specify:)	
MAD		
Attach to this application a topographic map of the area extending the outline of the facility, the location of each of its existing and treatment, storage, or disposal facilities, and each well where it injurates bodies in the map area. See instructions for precise requirement	proposed intake and discharge struct ects fluids underground, Include all	ures, each of its hazardous waste
XII. NATURE OF BUSINESS (provide a brief description)		
CBI Research Corp. provides R&D for the entire side related funded Research. CBI Industries construction of large metal plate products, sa service industry to other industries, utili principal products include petroleum, petropressure or vacuum vessels, nuclear reactor at temperature and cryogenic liquefaction and st spiral cases, tunnel liners and surge tanks, converter vessels, tanks and bins for granula and specialty gases such as CO2 to industry.	is engaged in the desig tructures and related sy ties and governmental bo- hemical and chemical sto nd containment vessels, orage facilities, hydroe fixed and shipmounted ma	n, fabrication and stems, and thus acts as dies. The company's rage tanks, process and water storage tanks, low lectric penstocks, rine structures, oxygen
XHL CERTIFICATION (see instructions)		は同じない。
I certify under penalty of law that I have personally examined and attachments and that, based on my inquiry of those persons immapplication, I believe that the information is true, accurate and confalse information, including the possibility of fine and imprisonment	nediately responsible for obtaining to mplete. I am aware that there are signal.	he information contained in the unificant penalties for submitting
DON HAGIROM OF RESEARCH	on Haystery	2/17/85
COMMENTS FOR OFFICIAL USE ONLY		



HAZARDOUS WASTE PERMIT APPLICATION Consolidated Permits Program

I. EPA I.D. NUMBER HTI 1010121213191518181

RCRA	42	D 4 #		17	This inform	nation is requ	ired un	der Sec	tion	005	0/ RC	CRA.I	الله الله		010 01	112		, 3	0	<u>-</u>
		AL USE			中では		48.0	e Programme de la companya della companya della companya de la companya della com	- J.	Ö.	7.0			1		を開				Ē
APPLICA	VED	DATER	4 day	<u> </u>	•							MMENTS								_
	}			_}	٠.							,								
II FIRS	TOR	REVISE	D APPI	ICATI	ON S				SE C		(1937) (1937)	HE STORY	(2) To 2						Y54	Ŧ
Place an	"X" in	the approx	oriate bo	x in A o	r B below	(mark one b	ox only	/ to inc	icate	wnet	ner tr	ns is the first a	opiication	YOU B	re submiti	ing fo	ryou	facii	ity of	`a. 'a
		on, If this er in Item		first app	lication an	nd you airead	ty know	your!	acility	's EF	A 1.0). Number, or i	f this is a	revised	l applicati	on, en	ter yo	ur fai	ality'	\$
A. FIRS	TAPE	PLICATION	ON (pla			nd provide t														_
	1. EX15	TING FA	CILITY		rructions / ete item be	or definition elow.)	of "ex	isting"	facilit	у.			T.HE	N FAC	ILITY (C	omple: FOR				: 5
<u> </u>	<u> </u>	40. 2.				LITIES. PR								-0.	٥٨٠	PROV	10. d	THE day)	DATE	
8	بر لبا	, 	/iusa		ces to the			55 . A	•		_		77 74	173	1	EXPE				~
B. REV	ISED	APPLICA	MOIT	•		w and comp	iele lie	m / 400	vej				∀							_
71		LITY HA				0.07122	0,000	est a Basis	- (a) (b)	250	ক্ষান্ত	the state of the s		CILIT	7 MAS A	TO CHA	PER	MIT	SF 18	=
						PACITIES		245-516					Carbon and the second		201404					÷
												ich process to b will be used th								
descri	pe the t	process (in	cluding i	ts design	capacity,	in the space	provid	ed on the	he for	m (/:	em II	I-CI.								
		ESIGN CA			eech code	entered in co	olumn A	enter :	the ca	pacit	y of t	he process.			٠.					
2. UN	NIT OF	MEASUR	E - For	each am						de fro	ותו החכ	e list of unit m	esure co	des bel	ow that di	scribe	s the	unit (of	
	instance of	ised. Only	الله والله المحاسمة	PRO-	. •	are listed bel PRIATE UN		٠		•	-: : -	المحادث ومدري المار	•	PRO-	APPRO	PRIA	TE UI	vr TS	OF:	7
		DCESS		CESS	MEASL	JRE FOR PE	ROCESS		:		PA	OCESS		CESS	· MEASU		OR P	30C		
Storage								_	Tree	mer		<u> </u>				دسده		<u> </u>		•
TANK		(barrel, dr.	um, etc.)	502		S OR LITE			TAP	1K	•	٠,		TOT	GALLO			YOR		
WASTE				303	CUBIC M							POUNDMENT		TOZ	GALLO	PERE	YAC			
Jisposai		OUNDMI	LNT	304	CALLOR	S OR LITE			INC	1 PK & 7	RATO	H.		TOR	TONS PI METRIC GALLO	TON	S PER	HOL		
INJECT	10N W	ELL		D79		S OR LITE		11	OTH	(FR)	(liee f	or physical, ch	emical	T04	LITERS GALLON	PERH	10U F			
LANDE	1			5.0	would co	uer one acre	:0 a	••	ther	mal o	or book	ogical treatment	16	, 0-	LITERS			1 0 4		
LAND				D#1	ACRES	E-METER			aton	. De	recabe	idments or inci	in							
OCEAN		POUNDME	NT	D63	LITERS	(5 PER DAY PER DAY (5 OR LITE			ine :	poce	provi	ded: Item III-4	,							
			•	UNIT							U	NIT OF .						UN	iT Or	:
UNIT O	F MF A	SUPE		MEAS CO		UNIT	FMFA	SURF		•		ASURE	UNIT	CE ME	ASURE			MEA	SUR DDE	
GALLO	NS					LITER	PERC	AY.				. v	ACRE	-FEET					. A	-
	YARDS					METRI	CTORS	PER H					ACRE	S	ETER.				. F . B	
GALLO	NS PEF	15 7 DAY			U	GALLO	PERH	IOUR .			.	, , H	HECI	ARES		• • • •		· · ·	. 😅	
						ine numbers cinerator th						ty has two ston	ige tanks	one to	ink can ho	10 200) galle	ns ar	id the	
ċi					اجا جا 🗸	77	77	7	\		7	777	77		77		7	$\overline{}$	$\overline{}$	
<u> </u>		DUP			<u> </u>			7		7	7	7 / / /	7	$\overline{77}$		$\overline{}$	<u> </u>	7	$\overline{}$	\
2 A PE	30	B. PR	OCESS	DESIG	SN CAPA	CITY	ļ -	OR	ER	A. P		B. PRO	CESS D	ESIG	Y CAPAC	-1TY		1 .	FOR	
=1	Σ.		1. AM	OUNT		OF MEA	OFF	ICIAL SE	E 10 E	CO	SS DE		1. AMOU	ит		OF	TINL	OF	FIC:. USE	A L
in about			(≠P €	cify),		(enter		4LY	25	300	n list					10	IRE Dier dei		NLY	
	10 110					27 19	7.	777		•	7	.,					11	77		=
(-1 S 0	2		600) 		G			5							!	<u> </u>			
(-= T 0	3		20)		E			6	1						į į			į	ļ
1-1	1-1					1 1-1	+	1 1		- 	' i					- 	- i-	1 1		<u>:</u>
1 150	$\{I\}$		100	0					7	!									-	! !
ــــ - م.ا.ر د			110	$\overline{\Gamma}$	·	IG	††		0	Ī	· · ·					 	-	 	Ť	<u> </u>
2 S C	111		110			1 10	11	1	8		11					11		1 1		!
3									9	- }										
4	 					1 1 1	++	1	10		1:	·				1 1	-} -	<u>; </u>	+	
								1 ()	. ([]	- 1	1 1					i i	1	1 1	1	1

7								
								•
	:				•			
								•
			,		•			
	4							
•					•			•
							•	
							•	
						•		•
						•		
						•		
		. •						
				•				
•								
handle hazardox tics and/or the t ESTIMATED A basis. For each	us westes which ar toxic contaminants LINAUAL QUANTI	e not listed in 4 of those hezard TY — For each xic contaminant	O CFR, S ous waster listed was	ubpart D, enter : L. sta entered in co	the four—digit nu olumn A estimate	part D. for each listed hamber(s) from 40 CFR, Single the quantity of that wanted quantity of all the notations.	ubpart C that describ	bes the characteris- adled on an annual
UNIT OF MEA	SURE — For each	quantity enters	ed in colur	mn 8 enter the	unit of messure o	code. Units of measure w	rhich must be used a	nd the appropriate
								CDE
E	VGLISH UNIT OF	MEASURE		CODE	METRIC	UNIT OF MEASURE		UUE
H facility recommendation the application of the ap	ounds	nit of measure is specific gravity or each (latted he stored, treater	for quanti of the war azardous y d, and/or o	ty, the units of ste. weste entered in disposed of at the	METRIC measure must be column A select e facility.		e required units of n	K M neasure taking into
H facility recoms account the app PROCESSES 1, PROCESS C For firsted he to indicate he For non-list contained in that characte Note: Four extreme right 2, PROCESS DITE: HAZARDine than one EPA 1, Select one o	ds use any other useropriste density or ODES: exardous weste: Fow the weste, will be ted hazardous waste in Item III to indice existic or toxic content toox of Item IV-D ESCRIPTION: If OUS WASTES DEI Hazardous Waste if the EPA Hazardous if the EPA Hazardous waste of the EPA Hazardous waste	or each listed has stored, treated at all the processing of the pr	azardous of the wall display the same terms of the same terms and the same terms are terms are terms and the same terms are terms are terms are terms and the same terms are terms	ty, the units of ste. Ty, the units of ste. weste entered in disposed of at the disposed of at the disposed of at the disposed to will be used to codes. If more a space provided of rocess that will be an ONE EPA He on the form as ter it in column	MILOGE METRIC measure must be column A select e facility. taminant entered store, treat, and/ re needed: (1) Sin page 4, the line to used, describe in MAZARDOUS WA follows: A. On the same line	the code/s/ from the list in column A, select the or dispose of all the nor number and the addition the process in the space p ASTE NUMBER — Hazain complete columns 8,0	of process codes co code(s) from the list a—listed hazardous scribed above; (2) E tal code(s), rovided on the formations wastes that co	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the
PROCESSES 1. PROCESS C For listed he to indicate he for non-list contained in that characte Note: Four extreme right of the total contained on the contained of the contained o	DUNDS	or each listed has specific gravity or each listed has stored, treated attended in the production of the other and other entries of the production of the other and the production of the other and the production of the production	azardous of the wall of the wa	ty, the units of ste. Ty, the units of ste. Weste entered in disposed of at the tic or toxic continuity will be used to codes. If more a pace provided or rocess that will be an ONE EPA in on the form as the tit in column are titled to treat, indous Waste Nutline. Der that can be under the continuity was the column to treat, indous Waste Nutline.	measure must be column A select e facility. (aminant entered store, treat, and/or e needed: (1) Sin page 4, the line of used, describe in AZARDOUS Was follows: A, On the same listore, and/or discomper that can be used to describe it store.	the code/s/ from the list in column A, select the or dispose of all the nor nater the first three as denumber and the addition the process in the space p ASTE NUMBER — Hazzar ne complete columns B, Cose of the waste, a used to describe the waste, the hazzardous weste.	of process codes co code(s) from the literation of a code(s) from the literation of a code(s). The code(s) is code(s), and code(s) is code(s), and code(s) is code(s), and code(s) is code(s).	M measure taking into intained in Item III st of process codes wastes that possess enter "000" in the t. an be described by ng the total annual) on that line enter
H facility recoms account the application of the ap	DUNDS	or each listed has specific gravity or each listed has stored, treated attending the production of the	azardous of the wait of the wait of the wait of the wait of the sales that process of the form a process of the form and the sales of t	ty, the units of ste. Toty, the units of ste. weste entered in disposed of at the disposed of a codes. If more a codes, if more a codes, if more a codes, if more a codes, if more as the disposed of a codes and the disposed of a code and the dispose	MILOGE METRIC ME	converted into one of the code/s/ from the list in column A, select the or dispose of all the nor number and the addition the process in the space place. NUMBER — Hazar ne complete columns B.C. is used to describe the water hazardous waste. I — A facility will treat and the water is corrosive and it	of process codes co code/s/ from the limited hazardous scribed above; (2) East cook/s/, rovided on the formations wastes that cooks, and D by estimations to be confident of three non-listed of three non-lis	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the t. an be described by ng the total annual) on that line enter imated 900 pounds wastes. Two westes
H facility recoms account the application of the ap	ds use any other useroprists density or opposite density or to include the control opposite density of the density o	or each listed has specific gravity or each listed has stored, treated as all the production aminant. Led for entering (1); and (3) Enter shall be us Waste Number shall be us Waste Number to other the other than other than on estimated 200 sattment will be	azardous of the wait of the wait of the wait d, and/or of the sales that process of ter in the sales for a pilotopic of the sales to be the sales of	ty, the units of ste. Toty, the units of ste. weste entered in disposed of at the disposed of a codes. If more a codes, if more a codes, if more a codes, if more a codes, if more as the disposed of a codes and the disposed of a code and the dispose	MILOGE METRIC ME	converted into one of the code/s/ from the list in column A, select the or dispose of all the nor number and the addition the process in the space place. NUMBER — Hazar ne complete columns B.C. is used to describe the water hazardous waste. I — A facility will treat and the water is corrosive and it	of process codes co code/s/ from the limits of number of process codes co code/s/ from the limits of number of process. (2) East coos/s/, revided on the formation wastes that coos wastes that column D(2), and D by estimation aste. In column D(2) and dispose of an estimation of three non-listed signitable and there were contacted three son-listed signitable and there were contacted to the contacted three son-listed signitable and there were contacted to the contacted three co	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the t. an be described by ng the total annual) on that line enter imated 900 pounds wastes. Two westes
If facility recommended in the application of the a	DUNDS	or each listed has stored, treated attended for entering (1); and (3) Entering (1); and (3) Entering (1); and (3) Entering (1); and (4) Entering (4); and (5) Entering (5) Entering (6) Entering (6) Entering (7) Ent	azardous of the wall of the wa	ty, the units of sta; weste entered in disposed of at the tic or toxic continuity of will be used to codes. If more a codes, the tic or toxic continuity of the form as the tic of the form as the tic of the toxic column or used to treat, indous Waste Nucline, ber that can be users X-1, X-2, X-1, operation, In according to the contract of each per year of each per year of each per year of each per year of each serator and disposition.	MILOGE METRIC ME	the code/s/ from the list in column A, select the or dispose of all the nor need to the number and the addition the process in the space plaste. Hazar need to describe the water to describe the wate	of process codes co code/s/ from the limits of number of process codes co code/s/ from the limits of number of process. (2) East coos/s/, revided on the formation wastes that coos wastes that column D(2), and D by estimation aste. In column D(2) and dispose of an estimation of three non-listed signitable and there were contacted three son-listed signitable and there were contacted to the contacted three son-listed signitable and there were contacted to the contacted three co	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the i. an be described by ing the total annual) on that line enter imated 900 pounds wastes. Two westes will be an estimated
H facility recommended in the application of the indicate has been decommended in that character Notes: Four extreme right of the training of the country of the training of the training of the training of the country of the training of the tr	DUNDS	or each listed has specific gravity or each listed has stored, treated as: For each date all the production of the produ	azardous of the wall of the wall of the wall disable that process to ter in the size of the described ers and en cesses to ten a process to ten and en cesses to ten and en cesse	ty, the units of sta; weste entered in disposed of at the tic or toxic continuity of will be used to codes. If more a codes, the tic or toxic continuity of the form as the tic of the form as the tic of the toxic column or used to treat, indous Waste Nucline, ber that can be users X-1, X-2, X-1, operation, In according to the contract of each per year of each per year of each per year of each per year of each serator and disposition.	column A select e facility. caminant entered store, treat, and/or enseded: (1) Sin page 4, the line of used, describe to AZARDOUS Wastone, and/or discomper that can be used to describe the same little of	the code/s/ from the list in column A, select the or dispose of all the nor need to the number and the addition the process in the space plaste. Hazar need to describe the water to describe the wate	of process codes co code/s/ from the listed hazardous scribed above; (2) East code/s/, rovided on the formations wastes that code/s, and D by estimationste. In column D(2) and dispose of an estimation three non-listed significable and there were considered three son-listed significable and three son-listed significable significable son-listed significable sign	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the i. an be described by ing the total annual) on that line enter imated 900 pounds wastes. Two westes will be an estimated
H facility recome account the application of the ap	ds use any other useroprists density or or openists density or openists density or openists density or openists or the wasta will be described or toxic content to openist or toxic content to openist or toxic content to openist or toxic on the content of the EPA Hazardous Wasta of the EPA Hazardous Wasta of the EPA Hazardous Wasta of the ext line of the next line of the next line of the next line of the manual programmer of the content of	or each listed has specific gravity or each listed has stored, treated as a list produced for entering (1); and (3) Entering (1); and (3) Entering (1); and (3) Entering (1); and (3) Entering all the produced for entering all the other cannot be a code in a code in the other cannot be a code in the code in	azardous of the wait of the maracterist esses that process of the form of the control of the	weste entered in disposed of at the tic or toxic continuity will be used to codes. If more a space provided or rocess that will be AN ONE EPA Hon the form as ter it in column becaused to treat, indous Waste Nu line. Der that can be upers X-1, X-2, X-1 operation. In according to the column because of the col	column A select a facility. aminant entered store, treat, and/or enseded: (1) Sin page 4, the line of used, describe to the same tissore, and/or distore, and/or distore, and/or distore, and/or distore, and/or distore, and/or distore, and/or distore. The other distore, the other distore, and waste. The other is waste. The other is waste. The other can be compared will be in a land column of the column of	the code/s/ from the list in column A, select the or dispose of all the nor need to the number and the addition the process in the space plaste. Hazar need to describe the water to describe the wate	of process codes co code/s/ from the listed hazardous scribed above; (2) East code/s/, rovided on the formations wastes that code/s, and D by estimationste. In column D(2) and dispose of an estimation three non-listed significable and there were considered three son-listed significable and three son-listed significable significable son-listed significable sign	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the i. an be described by ing the total annual) on that line enter imated 900 pounds wastes. Two westes will be an estimated
H facility recommended in the application of the ap	DUNDS	or each listed has specific gravity or each listed has stored, treated at all the product of the stored of the sto	azardous in discount of the wall of the wa	weste entered in disposed of at the tic or toxic continuity of will be used to codes. If more a codes, the tic or toxic continuity of the tic or	column A select a facility. aminant entered store, treat, and/or enseded: (1) Sin page 4, the line of used, describe to the same tissore, and/or distore, and/or distore, and/or distore, and/or distore, and/or distore, and/or distore, and/or distore. The other distore, the other distore, and waste. The other is waste. The other is waste. The other can be compared will be in a land column of the column of	the code/s/ from the list in column A, select the or dispose of all the nor need to the number and the addition the process in the space plaste. Hazar need to describe the water to describe the wate	of process codes co code/s/ from the listed hazardous scribed above; (2) East code/s/, rovided on the formations wastes that code/s, and D by estimationste. In column D(2) and dispose of an estimation three non-listed significable and there were considered three son-listed significable and three son-listed significable significable son-listed significable sign	M measure taking into intained in Item III st of process codes wastes that possess Enter "000" in the i. an be described by ing the total annual) on that line enter imated 900 pounds wastes. Two westes will be an estimated

C. SPACE FOR ADDITIONAL PROCESS CODES OR FOR DESCRIBING OTHER PROCESSES (COOK "TOH"). FOR EACH PROCESS ENTERED HERE INCLUDE DESIGN CAPACITY.

NOTE: Photocopy this page before completing if you have more than 25 wastes to list FOR OFFICIAL USE ONLY WI 29 Š 10 W DUP DUP DESCRIPTION OF HAZARDOUS WASTES (confinued) IV. D. PROCESSES B. ESTIMATED ANNUAL QUANTITY OF WASTE HAZARD. SURE (enter code) WASTENO 2. PROCESS DESCRIPTION (If a code is not entered in D(1)) 1. PROCESS CODES NO. (enter) (enter code) 29 17 29 | 17 7 P o, 10 00 1 0 0 0 0 BRULINE 3 0 8 0 10 SMIUM 0 O 10 A2108 84D1.7-0 5 0 -YON 105 20 0 6 00 · ALGTANE 7 20 01 0 0 20 8 01 0 Ì BENZEVE 7 P 4-00 0 9 0 P BONZIONE 0 0 10 0 THOIP OF P 0 11 a BRIMIDE 0 P CHILDRUFTER 01 12 0 0 BYLIVL 2 01 13 10 ALETATE FORM 01 14 10 HADEPER 15 0 FURIDE BADROPE 16 SYLTIDE 1508VIYL 2,0 17 0 ALCHOL MALTIC (0 0 (18 BURYDELDE MERCURY P 10 19 0 10 0 20 METHANDL P WEX 0-1 10 21 M ETAYL P 20 0 ISPOUTYL KETOWE MAPTHALINE 0 NITRUBBICZONE 10 0 0 PHENIL Š 0 10 PHIHALIC Q1JA 26 10

Sangaration assets

					is page pefore completing if you see (enter from page 1)	hen	T moi	7	than 25 y		SE OFFIC	IAL USK	Form Approved OMB No. 158-580004
WI 1		الاا	D		21913191518191			,	W		DUP	····	TIZ DUP
1	DES	لببا			N OF HAZARDOUS WAST	ES	CON	7				SA SOCIETY	
_		A. E	PA		B. ESTIMATED ANNUAL	C.	UNI	T.					D. PROCESSES
LINE NO.	W.A.	AZ, ST nter	E١	147	QUANTITY OF WASTE	7	ode)			(4 1	E33 CODE		2. PROCESS DESCRIPTION (If a code is not entered in D(1))
27	u		9	6	10 PYRIDHUE		P		30,1			111111111111111111111111111111111111111	
28	U	2	1	3	1 O TETRANYOROM	الحام	P		SOI				
29	Ц	7	1	9	O THIDVELA		P		301			' '	
30	4	2	λ	0	50 Towars		P		SOI				
31.	4	2	2	3	4000 TOLUGAT	. :	P .	•	102				
32	4	a	2	6	400 TCA		P		102				
33	4	2	3	9	100 30120125		Pi		501				
34	F	0	0	2	1000		H		SOI				
35	D	0	0	1	1000		P.		201				·
-				1					-1-1-				`
				-					7 1			, ,	
)		:								1 . 1	
	-			;	•				F 1	-		, -,	
		-	-								1		
	1								- 1 1				
												()	
	İ].	ĺ	-					i		, ,	1 7	
		İ	1	i					1 1	' '		, ,	
	-	1		!	·					'		, ,	
		į							-11-				
_	1	1							-	<u> </u> ' '	1 '	, ,	
											1 1		
	7;	-					,,	-	:7 . 11	1 27 - 29	1 17 . 29	:7 • 17	
A F	om	251	C-3	16-	80)		,		PAGE	3	OF 5		CONTINUE ON REVERSE
											•		

	•	/	•
		·	
•			
'	•		
			- '
	•	·	
			·
·	•	· .	
	•		
EPA I.D. NO. center from page 1:	· ·	-	_
FILDO829395188775	•		
V FACILITY DRAWING			
All existing facilities must include in the space provided VI. PHOTOGRAPHS	on dage 5 a scale drawing of the facility (see	instructions for more detail).	BACK ON BUILDING
All existing facilities must include photographs i	(aerial or ground—level) that clearly deli-	near all existing structures; existing sta	
treatment and disposal areas; and sites of future			nage,
VIL FACILITY GEOGRAPHIC LOCATION			
LATITUDE (degrees, minutes, & sect	onds) į	ONGITUDE (degrees, minutes, & seconds)	
411371025		088112007	-
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	
VIII. FACILITY OWNER			
A. If the facility owner is also the facility operator skip to Section IX below.	r as listed in Section VIII on Form 1, "General	i Information", place an "X" in the box to t	he left and
3. If the facility owner is not the facility operator	as listed in Section VIII on Form 1, complet	the following items:	
1. NAME OF F	CILITY'S LEGAL OWNER	2. PHONE NO. (a.	rea code & no.,
		29 36 - 16 33 - 6	<u> </u>
1. STREET OR P.O. BOX	4. CITY OR TO	NN 5. ST. 6. ZIP	CODE
F	<u> </u>		
IX. OWNER CERTIFICATION			
I cartify under penalty of law that I have personal	ally examined and am familiar with the	nformation submitted in this and all at	tached
cocuments, and that based on my inquiry of tho	se individuais immediately responsible f	or obtaining the information, I believe	that the;
submitted information is true, accurate, and com-		ant penalties for submitting false inform	nation,
including the possibility of fine and imprisonmer		·	
MODE BAH MOTO	B. SIGNATURE	C. DATE SIGNED	
2 - 11 1111	Lou Hagolion	Z/17/88	ı e
Y ORER TOR CERTIFIC TION			
X. OPERATOR CERTIFICATION			
I certify under penalty of law that I have personal accuments, and that based on my inquiry of tho			
submitted information is true, accurate, and coming the possibility of fine and imprisonmen	plete. I am aware that there are signific.		
A. NAME (PRR) OF TYPE	8. SIGNATURE	C. DATE SIGNED	
	<u> </u>		

E. USE THIS SPACE TO LIST ADDITIONAL PROCESS CODES FROM ITEM O(1) ON PAGE 1.